



Description

DVB-S to IP streaming equipment. SS-100 broadcast multicast streams and TV/Radio channels, selected from a DVB-S transponder (maximum 8), from a digital satellite reception, over a TCP-IP network. Mounted in 19" rack SP-725 (Cod.9120136).

CODE	9150000
MODEL	SS-100
TV system	DVB-S -> IP EN 300421
Reception	QPSK
Frequency range	950-2150 MHZ
Frequency step	1 MHz
A.F.C.	+/- 3 MHz
Input level	40...95 dBuV
Capture range	+/- 5 MHz
LNB power supply	+12 Vdc 350mA (máx.)
Symbol rate	1...60 Mbaud
F.E.C.	Auto, 1/2, 2/3, 3/4, 5/6, 7/8 (DVB: EN 300421)
Diplexing through loss	1,0 +/- 0,2 dB +/-TOL
TV/RADIO programmes per streamer	8
Number of filtered PIDs	64
Output bit rate	10/100 Mbps
Throughput max. by streamer	50 Mbps
Ethernet output	Full duplex / Half duplex / Auto MDIX
Supported protocols	Ipv4, UDP, RTP, ARP, ICMP, HTTP, TELNET
Streaming format	Multicast
Return loss	>15
Connectors	F female, RJ-45
Power supply	3,3 / 5,2 / 12,0 Vdc 475 / 185 / 12+LNB mA
Operating temperature close to equipment	-10...+65 °C
Room temperature with/without fan	- 10...+55/+45 °C
Protect ion index	IP 20C
Units per packing	1
Packing weight	1,40 kg
Packing dimensions	270 x 170 x 38 mm