



Description

A/V to IP streaming equipment. SV-200 broadcast multicast streams, selected from an A/V device (maximum 2), over a TCP-IP network. Mounted in 19" rack SP-725 (Cod.9120136).

JACK-RCA (CST-200) cable not included.

CODE	9150045
MODEL	SV-200
Input channels	2 x PAL (selectable)
Video codecs	MPEG-2/H.262 (ISO/IEC 13818-2 MP@ML)
Audio codecs	MPEG-1 Layer 2 (ISO/IEC-11172-3)
Video input level	0,5 - 1,4 Vpp
Audio input level	0,3 - 1 Vrms
Resolution	PAL: 352 x 288 / 352 x 576 / 720 x 576
Number of frames	50
Programmes per streamer	2
Output bit rate	10/100 Mbps
Throughput max. by streamer	27 Mbps
Ethernet output	Full duplex / Half duplex / Auto MDIX
Supported protocols	Ipv4, UDP, RTP, ARP, ICMP, HTTP, TELNET
Streaming format	Multicast UDP, RTD
Service advertising	SAP (RFC 2974), SDP (RFC 2327)
Connectors A/V	2 x Stereo A/V Mini Jack
Connectors Jack	GND, V, R, L
Power supply	3,3 / 5,2 560 / 580
Power consumption	4,2W
Operating temperature	-10...+65 °C
Room temperature with/without fan	-10...+55/+45 °C
Protection index	IP20C
Units per packing	1
Packing weight	1,40 kg
Packing dimensions	270 x 170 x 38 mm